

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: **2000** LBS. TRAILER WEIGHT & **200** LBS. TONGUE WEIGHT.
DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.

PARTS LIST/LISTE DE PIÈCES

Num	QTY	DESCRIPTION	Num	QTY	DESCRIPTION
1	4	LOCK WASHER 1/2	7		
2	4	FLAT WASHER 1/2	8		
3	4	HEX BOLT M12 X 40 X 1.75	9		
4	4	FLAT WITH NUT	10		
5			11		
6			12		FILAGE SUGGÉRÉ / WIRING: 119147



INSTALLATION :

- Abaisser le silencieux en enlevant les 2 supports de caoutchouc de chaque cotés.
- Agrandir le trou au châssis (indiqué sur image 1) à l'aide d'un foret étagé de chaque cotes du châssis .
- Insérer les plaques avec écrou soudé à l'intérieur du chassis pour chaque trou .
- Fixer avec les boulons fournis.
- Serrer tous solidement.

SRG trailer hitches., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, SRG trailer hitches Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. SRG trailer hitches Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.