



**FORD
FUSION 2013
HYBRID/STANDARD**

20535MT

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: **2000** LBS. TRAILER WEIGHT & **200** LBS. TONGUE WEIGHT.
DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.

PARTS LIST/LISTE DE PIÉCES					
Num	QTY	DESCRIPTION	Num	QTY	DESCRIPTION
1	4	LOCK WASHER 1/2	7		
2	4	FLAT WASHER 1/2	8		
3	4	HEX BOLT M12 X 40 X 1.75	9		
4	4	FLAT G.N. centré	10		
5			11		
6			12		FILAGE SUGGÉRÉ / WIRING: 119176



INSTALLATION:

- RETIRER LE PLASTIQUE DÉCORATIF DU PARE-CHOC.
- INSÉRER LES "FLAT NUT" À L'INTÉRIEUR DU CHASSIS.
- METTRE L'ATTACHE EN PLACE ET BOULONNER LE TOUT SOLIDEMENT.
- REMETTRE LE PLASTIQUE EN PLACE ET FAITE LA DÉCOUPE NÉCESSAIRE.
- REMOVE THE DECORATIVE PLASTIC BUMPER.
- INSERT THE FLAT NUT INSIDE THE FRAME.
- PUT THE HITCH IN PLACE AND THIGHTEN WELL.
- REPLACE THE DECORATIVE PLASTIC BUMPER AND MADE THE NECESSARY CUTTING.

SRG trailer hitches., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, SRG trailer hitches Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. SRG trailer hitches Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.