


GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: **3500** LBS. TRAILER WEIGHT & **350** LBS. TONGUE WEIGHT.  
\*\*\*DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.\*\*\*

### PARTS LIST/LISTE DE PIÈCES

Num	QTY	DESCRIPTION	Num	QTY	DESCRIPTION
1	4	HEX BOLT M12 X 50 X1.75	7		
2	4	FLAT WASHER 1/2	8		
3	4	LOCK 1/2	9		
4	2	FLAT GROS NUT DECENTRE WITH BRUSH	10		
5	2	FLAT GROS NUT CENTRE	11		
6			12		



## INSTALLATION :

1. Abaisser les silencieux.
2. Agrandir le trou arriere pour inserer les flat avec nut tel qu'indiqué au plan
3. Serrer les boulons solidement
4. Remettre en place les silencieux

SRG trailer hitches., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, SRG trailer hitches Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. SRG trailer hitches Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.