

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: **3500** LBS. TRAILER WEIGHT & **350** LBS. TONGUE WEIGHT.  
 \*\*\*DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.\*\*\*

PARTS LIST/LISTE DE PIÈCES

Num	QTY	DESCRIPTION	Num	QTY	DESCRIPTION
1	2	LOCK WASHER 1/2	7	2	FLATS CENTRÉS GROSSES NUTS
2	2	FLAT WASHER 1/2	8		
3	2	HEX BOLT M12 X 40 X 1.75	9		
4	4	LOCK WASHER M10	10		
5	4	FLAT WASHER 3/8	11		
6	4	HEX BOLT	12		FILAGE SUGGÉRÉ / WIRING: 119176



### INSTALLATION:

METTRE L'ATTACHE EN PLACE ET BOULONNER AVEC LES BOULONS  
 10mm X 1.25 X 40 SOUS LE CHASSIS ET LE BOULON 12 X 1.5 X 40 VERS L'AVANT DU VÉHICULE.

SERRER LE TOUT SOLIDEMENT.

PUT THE HITCH IN PLACE BOLT WITH BOLTS 10mm X 1.25 X 40 UNDER THE FRAME AND  
 TO BOLT WITH BOLT 12 X 1.5 X 40 TO THE FRONT OF THE VEHICLE.

THIGTEN WELL.